

## "V" Series Fiberglass Top Mount Filter

### Highlight Features:

- Suggested Installation: Domestic In-ground and above ground pool / hot spa tub
- Max operating pressure 36 psi / 2.5 bar
- Max temperature of 43°C (109 °F)
- Universal standard of union connection provided
- Suggested size of media : 0.5-0.8mm



V350-V700



V700(B)-V1400

### FEATURES

Bobbin-wound fiberglass reinforced tank is still the most popular standard in the industry after all. With UV-resistant surface finish, it is able to operate under prolong sunlight for years of reliability. "V" Series (V350-V1400) filters are equipped with a six-position, 1.5", 2", & 2.5" multiport valve and ABS laterals.

### Technical Information

Code	Model No	Filter Area(m <sup>2</sup> )	Valve Connections		Max Flow Rate		Sand(kg)
88010101	V350	0.09	1.5 inch	50mm	72lpm	4.32m <sup>3</sup> /h	20
88010102	V400	0.13	1.5 inch	50mm	108lpm	6.48m <sup>3</sup> /h	35
88010103	V450	0.16	1.5 inch	50mm	135lpm	8.10m <sup>3</sup> /h	45
88010104	V500	0.22	1.5 inch	50mm	185lpm	11.10m <sup>3</sup> /h	85
88010105	V650	0.32	1.5 inch	50mm	260lpm	15.60m <sup>3</sup> /h	145
88010107	V700	0.40	1.5 inch	50mm	325lpm	19.50m <sup>3</sup> /h	210
88010608	V700(B)	0.41	2.0 inch	63mm	336lpm	20.16m <sup>3</sup> /h	215
88010609	V800	0.50	2.0 inch	63mm	415lpm	24.90m <sup>3</sup> /h	355
88010610	V900	0.64	2.0 inch	63mm	520lpm	31.20m <sup>3</sup> /h	470
88010650	V900(C)	0.64	2.5 inch	75mm	533lpm	32.00m <sup>3</sup> /h	470
88010611	V1000	0.79	2.0 inch	63mm	650lpm	39.00m <sup>3</sup> /h	620
88010651	V1000(C)	0.79	2.5 inch	75mm	658lpm	39.50m <sup>3</sup> /h	620
88010613	V1200	1.13	2.0 inch	63mm	860lpm	51.60m <sup>3</sup> /h	860
88010652	V1200(C)	1.13	2.5 inch	75mm	941lpm	56.50m <sup>3</sup> /h	860
88010614	V1400	1.54	2.5 inch	75mm	1277lpm	76.90m <sup>3</sup> /h	1350

Note: Suggested sand weight varies with differences in filter media size. For reference only.



**SANTECO CONSTRUCTION  
SUPPLIES AND SERVICES**  
TEL NO. 9565078 / 09255259745